



Sensor Port
 3/8" Compression gland Standard.
 Available :
 1/8"
 1/4"
 1/2"
 Titanium dry well.

Specifications for Ti-HXM Heat Exchangers (Direct Expansion)

MODEL NO.	NOMINAL BTUH	REFRIGERATION CONNECTIONS		WATER IN/OUT	WATER FLOW (GPM)		A	B	C
		Liquid	Suction		MIN	MAX			
TI-HXM-0D	1/5	3/8"	3/8"	1" FPT	10	40	13 1/2"	7 1/2"	7 1/4"
TI-HXM-1D	1/4	3/8"	3/8"	1" FPT	10	40	13 1/2"	7 1/2"	7 1/4"
TI-HXM-2D	1/3	3/8"	3/8"	1" FPT	10	40	13 1/2"	7 1/2"	7 1/4"
TI-HXM-3D	1/2	1/2"	1/2"	1" FPT	10	40	15 1/2"	9 1/2"	7 1/4"
TI-HXM-4D	3/4	1/2"	5/8"	1" FPT	10	40	19 1/2"	13 1/2"	7 1/4"
TI-HXM-5D	1	1/2"	5/8"	1" FPT	10	40	23 1/2"	17 1/2"	7 1/4"

1. Specifications subject to change without notice.
2. Nominal horsepower rating based on 12,000 Btuh @ 75°F water temperature.
3. Dimensions may vary, if size is critical please contact UMI to discuss options.
4. Brass 45° SAE Male Flare Fittings.
5. Flow rate requirements are relative to water temperature. As a rule, colder water requires higher flow rates.

UMI
 Universal Marine Industries
 2790 Sunnyside Rd,
 Anmore, BC V3H3C8
 Canada