



Specifications for Ti-HXU Heat Exchangers (Direct Expansion)

MODEL NO.	SHELL SIDE 10"			TUBE SIDE 2	Nominal Capacity 3		DIMENSIONS 1			
	PD (psi)	FLOW RATE Min/Max (GPM)	INLET / OUTLET	INLET/ OUTLET	BTU	KWH	A	B	C	D
Ti-HXU-40D	1.5	75 /150	2 ½"	7/8" / 1 3/8"	480,000.0	140.67	127"	114"	20"	16"
Ti-HXU-35D	1.5	75 /150	2 ½"	7/8" / 1 3/8"	420,000.0	123.08	127"	114"	20"	16"
Ti-HXU-30D	1.5	75 /150	2 ½"	7/8" / 1 3/8"	360,000.0	105.50	127"	114"	20"	16"
Ti-HXU-25D	1.5	75 /150	2 ½"	7/8" / 1 3/8"	300,000.0	87.12	127"	114"	20"	16"
Ti-HXU-20D	1.5	75 /150	2 ½"	7/8" / 1 3/8"	240,000.0	70.33	65"	54"	20"	16"
Ti-HXU-15D	1.5	75 /150	2 ½"	7/8" / 1 3/8"	180,000.0	52.75	65"	54"	20"	16"
Ti-HXU-10D	1.5	75 /150	2 ½"	7/8" / 1 3/8"	120,000.0	35.16	65"	54"	20"	16"

1. Dimensions may vary, if size is critical please contact UMI to discuss options.
2. 90° Rotalock sweat connections (360° vectoring) on Refrigeration side
3. 68°F (20°C) water on process side @ 100gpm

Options: SCH 80 And CPVC material shell construction
 316 SS. or Marine grade Aluminum Mounting frame. (Wall mount, Floor mount or Vertical mount.)
 316 Stainless steel hardware.

UMI
 Universal Marine Industries
 2790 Sunnyside Rd,
 Anmore, BC V3H3C8
 Canada

TITLE:
 Ti-HXU 10 Thru 40D Heat Exchanger :Direct Expansion

Last Update: 12-04-2009

Date: 11-11-2009

BY: EK