



Model No.	HP	Nominal BTUH	Amps @ VAC, 1Ø		Refrigerant	Nominal Flow Rate*2	Water Connection	Ship Wt (lbs)	Dimensions				
			115 Volts	208/230 Volts					L	W	H	A	B
Ti-CHAM-0	1/5	1,800	3.9		134a	5-40	1" FPT	51	20	18	12	8"	4"
Ti-CHAM-1	1/4	3,000	4.9		134a	10-40	1" FPT	58	20	18	12	8"	4"
Ti-CHAM-2	1/3	4,000	7.3		134a	10-40	1" FPT	65	20	18	12	8"	4"
Ti-CHAM-3	1/2	6,000	9.3		134a	10-40	1" FPT	90	21	22	13	10"	5"
Ti-CHAM-4	3/4	9,000	15	7.1	22 3	10-40	1" FPT	145	27	26	16	14"	5"
Ti-CHAM-5	1	12,000		7.3	22 3	10-40	1" FPT	165	27	26	16	18"	5"

1. Specifications subject to change without notice.
2. Flow rate requirements are relative to water temperature. As a rule, colder water requires higher flow.
3. R-22 replacement R417a available on request.
4. Optional Safety flow switch plumbed and wired.



TITLE: Ti-CHAM-0 thru
Ti-CHAM-5
CHILLER SPECIFICATIONS

Last Updated:

Date:

BY: EK